

## Puncture Proof Polyurethane Plate Swivel Castor Brake 260mm 100kg Load

**Product code: BZFPC260PPUBJDBK/LITE**

Fabricated swivel castor with a top plate fixing fitted with a black diamond pattern puncture proof tyre red polypropylene centred wheel with ball bearing and a side fitting wheel brake. Wheel diameter 260, tread width 85mm, overall height 318mm, plate size 115mm x 105mm, hole centres 92mm x 67mm or 76mm x 76mm. Load capacity 100kg.



|                          |  |
|--------------------------|--|
| Diameter (mm)            | 260  |
| Castor Type              | Swivel with Wheel Brake                                  |
| Fixing Option            | Plate  |
| Plate Size (mm)          | 115 x 105  |
| Height (mm)              | 318  |
| Hole Centres (mm)        | 76/92 x 76/67  |
| Swivel Radius (mm)       | 205  |
| Tread (mm)               | 85   |
| Temperature Resistance   | -10 °C TO +60 °C   |
| To Suit Fixing Bolt (mm) | 10   |
| Bearing Type             | Ball   |
| Wheel Material           | Puncture Proof Wheels                                    |
| Load Capacity (kg)       | 100  |
| Colour / Shore Hardness  | Black Puncture Proof Tyre on Polypropylene Rims / Low PU |
| Top Plate Thickness (mm) | 5  |
| Fork Thickness (mm)      | 5  |