

Removable Handle Elastic Rubber Cast Iron Plate Swivel Castor 150mm 350kg Load

Product code: JAZHS150CRBJRH



Side winding jacking unit (removable handle) with maximum lift of 200mm fitted with a Fabricated swivel castor with a top plate fixing fitted with a black elastic rubber tyred cast iron centred wheel with ball bearings. Wheel diameter 150mm, tread width 50mm, Load for the complete unit is capacity 350kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. for other dimensions please refer to the BIL catalogue or request a drawing. When jacked up to the height please be aware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. **DO NOT OVERWIND** Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)

| | |
|--------------------------|--|
| Diameter (mm) | 150 |
| Castor Height (mm) | 190 |
| Castor Type | Swivel |
| Swivel Radius (mm) | 120 |
| Fixing Option | Plate |
| Bearing Type | Ball |
| To Suit Fixing Bolt (mm) | 10 |
| Wheel Material | Rubber on Cast Iron |
| Colour / Shore Hardness | Black Elastic Rubber on Cast Iron Rim / 75 Shore A |
| Temperature Resistance | -20 °C TO +60 °C |
| Load Capacity (kg) | 350 |
| Tread (mm) | 50 |
| Height (mm) | 597 / 797 |
| Lifting Stroke (mm) | 200 |
| Handle Option | Removable |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

