



Removable Handle Elastic Rubber Cast Iron Plate Swivel Castor Brake Locking Castor 200mm 450kg Load

Product code: JAZHS200CRBJSWBRH

Side winding jacking unit (removable handle) fitted with a fabricted swivel castor with a 200mm black elastic rubber tyred cast iron centred wheel with ball bearings and wheel brake, wheel to carry a maximum load caopicity of 450kg per complete unit. Please note Jacking castors are rated on a different princiable to other castors. They lift the load off the floor and therefore each castor is liable to carry half the total load, also please note the maximum lift is 200mm but when jacked up to the height please beaware of any obstacles as a sudden shock could result in the inner square tube bend around the outer tube. PLEASE NOTE: BIL do not recommend brakes on jacking castors. DO NOT OVERWIND Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit)



Diameter (mm)	200
Castor Height (mm)	241
Castor Type	Swivel with Total Lock Brake
Swivel Radius (mm)	156
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	10
Wheel Material	Rubber on Cast Iron
Colour / Shore Hardness	Black Elastic Rubber on Cast Iron Rim / 75 Shore A
Temperature Resistance	-20 °C TO +60 °C
Load Capacity (kg)	450
Tread (mm)	50
Height (mm)	648 / 848
Lifting Stroke (mm)	200
Handle Option	Removable





