

Removable Handle Polyurethane Cast Iron Plate Swivel Castor 150mm 1000kg Load

Product code: JAZHSK150PTBJ/WT/RH

Side winding jacking unit (removable handle)with maximum lift of 200mm fitted with a Fabricated swivel castor with a top plate fixing fitted with a brown polyurethane tyred cast iron centred wheel with ball bearings. Wheel diameter 150mm, tread width 60mm, maximum Load for the complete unit is capacity 1000kg. Please note Jacking castors are rated on a different principal to other castors and we recommend the total lifted load is divided over just 2 jacking units. for other dimensions please refer to the BIL catalogue or request a drawing. When jacked up to the height please be aware of any obstacles as a sudden shock could result in the inner square tube bending around the outer tube. **DO NOT OVERWIND** Handle excessively more than what is needed as this will cause the pin in the gearbox to shear. (This is a safety precaution against over loading the unit) (Catalogue SKU JAZHSK150PTBJRH/WT)



Diameter (mm)	150
Castor Height (mm)	200
Castor Type	Swivel
Swivel Radius (mm)	130
Fixing Option	Plate
Bearing Type	Ball
To Suit Fixing Bolt (mm)	10
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Brown Polyurethane on Cast Iron Rim / 94 Shore A
Temperature Resistance	-20 °C TO +80 °C
Load Capacity (kg)	1000
Tread (mm)	60
Height (mm)	607 / 807
Lifting Stroke (mm)	200
Handle Option	Removable

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

