

## Rubber Swivel Castor Brake Plate 50mm 50kg

**Product code: SSRA50GRSWB**



Grade 304 Pressed stainless steel swivel castor with a flange plate fitted with a grey thermoplastic rubber tyre on polypropylene centred wheel with a Plain Bore and a total lock brake. Wheel diameter 50mm, tread width 24mm, overall height 74mm. plate size 60mm x 60mm, hole centres 49.5mm x 49.5mm or 42.5mm, m x 42.5mm Load capacity 50kg

Diameter (mm)	50
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Height (mm)	74
Wheel Material	Rubber on Polypropylene
Colour / Shore Hardness	Grey Rubber on Polypropylene Rim / 87 Shore A
Bearing Type	Plain
Tread (mm)	24
Fork Thickness (mm)	1.8
To Suit Fixing Bolt (mm)	6
Load Capacity (kg)	50
Temperature Resistance	-15 °C TO +80 °C
Plate Size (mm)	60 x 60
Hole Centres (mm)	49/43 x 49/43
Top Plate Thickness (mm)	1.8
Swivel Radius (mm)	88

### BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

