

Rubber Swivel Castor Plate Brake 75mm 70kg

Product code: BZM75GRSWB

Pressed steel swivel castor with a top plate fixing fitted with a grey thermoplastic rubber tyre on polypropylene centred wheel with plain bore and a total lock brake. Wheel diameter 75mm, tread width 32mm, overall height 109mm, top plate 90mm x 70mm, hole centres 75mm x 56mm or 64mm x 44mm. Load capacity 70kg.



| | |
|--------------------------|---|
| Diameter (mm) | 75 |
| Fixing Option | Plate |
| Castor Type | Swivel with Total Lock Brake |
| Plate Size (mm) | 90 x 70 |
| Hole Centres (mm) | 64/75 x 44/56 |
| Height (mm) | 109 |
| Bearing Type | Plain |
| Swivel Radius (mm) | 95 |
| Wheel Material | Rubber on Polypropylene |
| Colour / Shore Hardness | Grey Rubber on Polypropylene Rim / 82 Shore A |
| Top Plate Thickness (mm) | 2 |
| Fork Thickness (mm) | 2 |
| Temperature Resistance | -15 °C TO +80 °C |
| To Suit Fixing Bolt (mm) | 8 |
| Tread (mm) | 32 |
| Load Capacity (kg) | 70 |

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

