

Soft Ergonomic Polyurethane Plate Swivel Castor Brake 125mm 450kg Load

Product code: BZPH125SRPTABJSWB

Pressed steel swivel castor with a flat top plate fixing fitted with a green 85 shore A ergonomic polyurethane tyred aluminium centered wheel with ball bearing and total lock brake. Wheel diameter 125mm, tread width 50mm, overall height 155mm, plate size 135mm x 110mm, hole centres 105mm x 80/75mm. Load capacity 450kg.



Diameter (mm)	125
Castor Type	Swivel with Total Lock Brake
Fixing Option	Plate
Height (mm)	158
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Green Ergonomic Polyurethane on Aluminium Rim / 85 Shore A
Temperature Resistance	-20 °C TO +80 °C
Bearing Type	Ball
Load Capacity (kg)	450
Tread (mm)	50
Swivel Radius (mm)	125
Plate Size (mm)	135 x 110
Hole Centres (mm)	105 x 80/75
Top Plate Thickness (mm)	4
Fork Thickness (mm)	4
To Suit Fixing Bolt (mm)	10

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

