


Soft Speed Polyurethane Plate Swivel Castor 160mm 550kg Load

Product code: BZXP160SPABJLP



Pressed steel swivel castor with a top plate fixing fitted with a blue 75 shore A polyurethane tyre on aluminium centred wheel with ball bearings. Wheel diameter 160mm, tread width 50mm, overall height 205mm, top plate 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 550kg at 4kph and 220kg at 16kph ****FOR INTERNAL TOWING ONLY****

Diameter (mm)	160
Load Capacity (kg)	550
Bearing Type	Ball
Fixing Option	Plate
Castor Type	Swivel
To Suit Fixing Bolt (mm)	10
Swivel Radius (mm)	140
Height (mm)	205
Plate Size (mm)	135 x 110
Hole Centres (mm)	140 X 105
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Polyurethane on Aluminium Rim / 75 Shore A
Tread (mm)	50
Top Plate Thickness (mm)	6
Temperature Resistance	-20 °C TO +70 °C
Fork Thickness (mm)	5

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

