

Soft Speed Polyurethane Plate Swivel Castor Brake 150mm 500kg Load

Product code: BZXP150SPABJSWBLP



Pressed steel swivel castor with a top plate fixing fitted with a blue 75 shore A polyurethane tyre on aluminium centred wheel with ball bearings and a total lock brake. Wheel diameter 150mm, tread width 50mm, overall height 200mm, top plate 175mm x 140mm, hole centres 140 x 105mm. Load capacity 500kg at 4kph and 190kg at 16kph ****FOR INTERNAL TOWING ONLY****

Diameter (mm)	150
Load Capacity (kg)	500
Bearing Type	Ball
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
To Suit Fixing Bolt (mm)	10
Swivel Radius (mm)	180
Height (mm)	200
Plate Size (mm)	162 X 140
Hole Centres (mm)	140 X 105
Wheel Material	Polyurethane on Aluminium
Colour / Shore Hardness	Blue Polyurethane on Aluminium Rim / 75 Shore A
Tread (mm)	50
Top Plate Thickness (mm)	6
Temperature Resistance	-20 °C TO +70 °C
Fork Thickness (mm)	5

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729