

Vulkollan Polyurethane Cast Iron Plate Swivel Castor 250mm 1350kg Load

Product code: BZQ250VPTBJ/50/M

Fabricated swivel castor with a top plate fixing fitted with a High grade Vulkollan polyurethane tyred cast iron centred wheel with ball bearings. Wheel diameter 250mm, tread width 50mm, overall height 314mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 1,350kg



| | |
|--------------------------|--|
| Diameter (mm) | 250 |
| Fixing Option | Plate |
| Castor Type | Swivel |
| Bearing Type | Ball |
| Height (mm) | 314 |
| Plate Size (mm) | 170 X 140 |
| Hole Centres (mm) | 140 X 105 |
| To Suit Fixing Bolt (mm) | 14 |
| Wheel Material | Polyurethane on Cast Iron |
| Colour / Shore Hardness | Vulkollan Polyurethane on Cast Iron / 92 Shore A |
| Temperature Resistance | -30 °C TO +80 °C |
| Top Plate Thickness (mm) | 12 |
| Fork Thickness (mm) | 10 |
| Swivel Radius (mm) | 210 |
| Load Capacity (kg) | 1350 |
| Tread (mm) | 50 |