

Vulkollan Polyurethane Cast Iron Plate Swivel Castor 300mm 1900kg Load

Product code: BZQ300VPTBJ/C



Fabricated swivel castor with a flat plate fixing fitted with a High grade Vulkollan polyurethane tyre on cast iron centred wheel with a ball bearing. Wheel diameter 300mm, tread width 80mm, overall height 365mm, plate size 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 1900kg at 6kph max speed.

Diameter (mm)	300
Fixing Option	Plate
Castor Type	Swivel
Bearing Type	Ball
Height (mm)	365
Plate Size (mm)	170 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Vulkollan Polyurethane on Cast Iron / 92 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Swivel Radius (mm)	232
Load Capacity (kg)	1900
Tread (mm)	80

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

