

Vulkollan Polyurethane Cast Iron Plate Swivel Castor Brake 200mm 1400kg Load

Product code: BZQ200VPTBJSWB



POA Fabricated swivel castor with a top plate fixing fitted with a High grade Vulkollan polyurethane tyre cast iron centred wheel with ball bearings and wheel brake. Wheel diameter 200mm, tread width 80mm, overall height 264mm, top plate 175mm x 140mm, hole centres 140mm x 105mm. Load capacity 1730kg static, 1400kg at 6kph. ****MANUFACTURED TO ORDER****

Diameter (mm)	200
Fixing Option	Plate
Castor Type	Swivel with Total Lock Brake
Bearing Type	Ball
Height (mm)	264
Plate Size (mm)	170 X 140
Hole Centres (mm)	140 X 105
To Suit Fixing Bolt (mm)	14
Wheel Material	Polyurethane on Cast Iron
Colour / Shore Hardness	Vulkollan Polyurethane on Cast Iron / 92 Shore A
Temperature Resistance	-30 °C TO +80 °C
Top Plate Thickness (mm)	12
Fork Thickness (mm)	10
Swivel Radius (mm)	167
Load Capacity (kg)	1400
Tread (mm)	80

BIL GROUP LTD

Porte Marsh Road, Calne, Wiltshire, SN11 9BW

Registered in England No: 2603821

VAT Reg: GB572705729

