


## DRAWING DISCLAIMER

COPYRIGHT OF THIS DRAWING IS RESERVED BY BIL GROUP LTD. IT IS ISSUED ON CONDITION THAT IT IS NOT REPRODUCED, COPIED, OR DISCLOSED TO A THIRD PARTY EITHER WHOLLY OR IN PART WITHOUT THE CONSENT IN WRITING OF BIL GROUP LTD.









Pressed steel fixed castor with a 10mm bolt hole fitted with a grey electrically conductive rubber tyre on polypropylene centred wheel with a plain bearing. Wheel diameter 75mm, tread width 24mm, overall height 101mm with a Load capacity 60kg. Conductive offers a resistance  $R\!<\!10 \mathrm{K}\Omega$ 





	NAME	DATE
DRAWN	Matt	12/12/17
APPROVED BY	Chris	12/12/17
SCALE	1:2	12/12/17
WEIGHT	0.149kg	12/12/17

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETRES

Unspecified Tolerances Machining ± 0.25mm Fabrication ± 1mm

7	(B	IL)
7		

BIL Group Ltd, Porte Marsh Road, Calne Wiltshire, SN11 9BW, United Kingdom Tel +44 (0)1249 822 222 Fax: +44 (0)1249 822 300 www.bilgroup.co.uk

TITLE

BZRAF75GRECBH10

SIZE DWG NO.  A4 BILCW03BZRAF75GRECBH10_01	L			
A4 BILCW03BZRAF75GRECBH1001	T	SIZE	DWG NO.	RE
		Α4	BILCW03BZRAF75GRECBH1001	1

FILE NAME BILCW03BZRAF75GRECBH10\_\_01.PDF

SHEET 1 OF 1